

**Bhagat Phool Singh Mahila Vishwavidyalaya**  
**Department of Engineering Cell**  
**Khanpur Kalan (Sonapat), Haryana-131305**

Office No. 01263-283007,283530, Fax No. 01263-283779, [www.bpswomenuniversity.ac.in](http://www.bpswomenuniversity.ac.in)

**NOTICE INVITING TENDER**

Sealed tenders as per schedule/DNIT attached are hereby invited on behalf of Registrar in her Office at BPSMV Khanpur Kalan through Registered post/speed post from the eligible contractor and L&C Societies the below noted work. If the date on which the tenders are to be received is declared holiday then the tender will be received on the next working day. The tender shall be opened on the same day in the presence of the tenderer or the authorized representative/agents who may like to be present at that time:-

Sr. No.	Name of Work	App. Cost. (In Thousand)	Time Limit	Date & Time for Receiving of Tender		Date & Time for opening of Tender	
				Date	Time	Date	Time
1.	Tender for renovation of House no. 247 in the campus of B.P.S.M.V. Khanpur Kalan.	71,500/-	<b>One month</b>	11.05.23	<b>1:00 pm</b>	11.05.23	<b>3:00 pm</b>

1. The rates of all items should be quoted on item rate basis.
2. The limited tender/quotation may be sent in favour of Registrar, BPSMV Khanpur Kalan, in sealed envelop through Registered Post/Speed Post with mentioning tender name in bold letter on the envelop.
3. Engineering –In-Charge is competent to increase/decrease the quantity of work.
4. Central/ State taxes will be deducted as applicable from time to time.
5. The supply shall be taken in the University as per specifications given in DNIT.
6. No extra payment will be done.

**SDE (Civil)**  
**For Registrar**

Endst. No./ BPSMV /Engg./23/

Dated

A copy of the above is forwarded to the following for information and necessary action:-

1. Notice Board.

**SDE (Civil)**

## DETAILED NOMINCLATURE.

**NAME OF WORK:-** Tender for renovation of House no. 247 in the campus of B.P.S.M.V. Khanpur Kalan.

**Approx. Cost :** Rs. 71,500/-

**Date of Tender:** 11.05.2023

Sr. No.	Description of items	Qty.	Unit	Rate to be quoted by the agency in words and in figures, FOR including VAT & taxes.	
				In Figure	In Word
1.	Distemping with 1st quality acrylic distemper (Ready mix)having voe content less than 50 grams/ litre of approved brand and manufacture to give an even shade: Old work (one or more coats) <b>(HSR30.25.1 )</b>	215.53	Sqm.		
2.	Finishing walls with Acrylic Smooth exterior paint of required shade: Old work (Two or more coat applied @ 1.67 litre/ 10 sqm) on existing cement paint surface <b>(HSR30.37 .1 )</b>	141.59	Sqm.		
3.	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete. <b>(HSR 30.22)</b>	75.12	Sqm.		
4.	Providing and applying two coats white cement based putty of approved brand and manufacturer, over plastered surface and grinding the surface smooth with sand paper to get en even and smooth finish including cost and carriage of all material , labour charges, scaffolding, sundries etc. complete <b>(HSR 11.58)</b>	75.12	Sqm.		
5.	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade One or more coats on old work. <b>(HSR 30.28.1)</b>	96.76	Sqm.		
6	Oxidised mild steel single acting spring hinges 150 mm <b>(HSR B0574)</b>	04	Each		
7	Dismantling wire gauze from door and window and putting in to rolls of items complete in all respect. <b>(Old HSR 8.14)</b>	14.82	Sqm.		
8	Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete. With 2nd class teak wood beading 62X 19 mm <b>(HSR 12.33.1 )</b>	14.82	Sqm.		
9	Renewing glass panes, with putty and nails wherever necessary including racking out the old putty: Float glass panes of nominal thickness 4 mm (weight not less than 1 Okg/sqm) <b>(HSR 30.54.1)</b>	0.82	Sqm.		
10.	Providing and fixing panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or	2.75	Sqm.		

	rebates to be measured). Panelling for panelled or panelled and glazed shutters 25 mm to 40 mm thick: Kiln seasoned and chemically treated Hollock wood <b>(HSR 12.9.2)</b>				
11	Providing and placing on terrace (at all floor levels) polyethylene water storage tank, IS: 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. <b>(HSR 22.181)</b>	500	Ltr.		
12	G.I. inlet connection <b>(HSR B1158 )</b>	2	Each		
13	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end): 32 mm nominal bor <b>(HSR 22.98.3)</b>	2	Each		
14	Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete : 20 mm nominal bore <b>(HSR 22.103.2)</b>	2	Each		
15	Providing and fixing C.P. brass long body bib cock of approved quality conforming to IS standards and weighing not less than 690 gms. 15 mm nominal bore <b>(HSR 22.106.1)</b>	3	Each		
16	Dismantling cement conglomerate / terrazzo floors 25 mm to 50 mm manually/ by mechanical means and disposal of material within standard lead as per direction of Engineer- in-charge <b>(HSR 5.42)</b>	3.25	Sqm.		
17	Dismantling W.C. Pan of all sizes including disposal of dismantled materials i/c malba all complete as per directions of Engineer-in-Charge. <b>(HSR 30.83)</b>	1	Each		
18	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift up to 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All kinds of soil. <b>(HSR 4.14.1)</b>	2.33	Cum		
19	Brick work with common burnt clay non-modular bricks of class designation 7 .5 in superstructure above plinth level up to floor IV level in all shapes and sizes in : Cement mortar 1:6 (1 cement: 6 coarse sand) <b>(HSR 7.22.2)</b>	0.11	<b>Cum</b>		
20	Cement Concrete 1:8:16 with Over burnt (Jhama) Brick Aggregate: 90 mm to 40 mm size in foundation and plinth. <b>(HSR 10.100.1)</b>	0.74	Cum		
21	Providing and fixing on wall face Unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes.110 mm diameter <b>(HSR 9.57.2)</b>	15	Rmt.		
22	Providing and fixing on wall face Unplasticised - PVC moulded fittings/ accessories for Unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS :5382,	2	Each		

	leaving 10 mm gap for thermal expansion. Single tee with door 110 mm <b>(HSR 9.58.3.2)</b>				
23	Providing and fixing on wall face Unplasticised - PVC moulded fittings/ accessories for Unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS :5382, leaving 10 mm gap for thermal expansion 110 mm Bend 87.5° <b>(HSR 9.58.5.2)</b>	5	Each		
24.	Providing and laying of conglomerate floor 50mm thick cement concrete topping 1 :2:4 <b>(HSR 10.7)</b>	9.64	Sqm.		
25	Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer), of 1st quality conforming to IS : 15622, of approved make, in all colours, shades, except White, Ivory,Grey, Fume Red Brown, laid on 20 mm thick bed of cement mortar 1 :4 (1 Cement : 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/including pointing the joints with white cement and matching pigments etc., complete. <b>(HSR 10.60)</b>	8.92	Sqm.		
26	Providing & fixing White vitreous china water closet squatting pan (Indian type) along with "S" or "P" trap including dismantling of old we seat and "S" or "P" trap at site complete with all operations including all necessary materials, labour and disposal of dismantled material i/c malba, all complete as per the direction of Engineer-in charge Long pattern W.C Pan of size 580x440 mm <b>(HSR30.84.1)</b>	1	Each		

**JE (Civil)**

**SDE (Civil)**